

# 1538H 4:3 PCAP

High Brightness Touchscreen




## Features

- + Open frame flat design, metal material
- + IP55 level front panel waterproof
- + Industrial grade LCD, LED backlight
- + Resolution 1024X768@60Hz
- + 1000nits brightness backlight
- + 10 point projection capacitive touchscreen
- + Cover plate anti riot and anti-glare coating
- + Bonded with UV-resistant optical glue
- + Sunlight adaptive adjustment module
- + Air-cooled circulation cooling method
- + Video interface: HDMI+VGA
- + Reserve side and back assembly holes
- + Support OS: Windows/Android/Linux
- + 2-years Warranty



## Optional:

- No Touch
- Touch interface: RS232
- 700-1200nits
- Cooling fan set
- Video interface: Display Port
- All-In-One (Android/Windows)



<b>TDS1538H High Brightness Open Frame Touchscreen Monitor</b>	
Diagonal	15''(4:3)
Color	Black/Silver
Native Resolution	1024X768@60Hz
Active Display Area	304.13X 228.10(mm)
Dimensions	354X 277X 52(mm)
Contrast Ratio	800:1
Number of Colors	262K
Viewing Angle	Horizontal: 80° /80°; Vertical:60° /80°
Brightness	LCD : 1000nits; PCAP: 835 nits
Brightness adjustment mode	*The brighter the ambient light, the brighter the LCD screen *The darker the ambient light, the darker the LCD screen, and enter the power saving mode
Response	30ms
Touch Technology	PCAP-10 点
Mode of touch	Fingers/silicone pen
Glass thickness	3mm, tempered, surface AG coating
Glass hardness	7H(Mohs)
Touch accuracy	≤2mm
Viewing Angle	USB 2.0
Video Interface	VGA+HDMI
Input Voltage	AC: 100-240 VAC,50/60 Hz
Power Supply	12V-19V8A(Power Jack : 2.1mmx5.5mm)
Waterproof	Front panel :Front frame touch screen sealed to bezel Back: dust hole(Option: no hole)
Explosion-proof	450 grams of steel ball height 1.2 meters vertical drop center point will not break
Cooling method	Cooling holes exchange external air flow
Temperature	Operating: 0°C-50°C; Storage:-20°C-80°C
Humidity	Operating: 20%-70%; Storage:10%-80%
Mounting Options	Back VESA two groups of holes: 75mm&100mm Each of the four sides has a set of fixing holes: 142mm
Weight(net)	3.7KG
Shipping Dimensions	450X340X135(mm)
Warranty	2- years
MTBF	50,000 hours
Agency Approvals	FCC; CE; ROHS
What's in the Box	1*HDMI Cable;1*USB Cable; 1*Power Cable