

TDS2739L 16:9 (Light bar)

Open - Frame Touchscreen



Features

- + Metal shell, open frame design
- + Flat and zero bezel appearance
- + Commercial grade LCD, LED backlight
- + Resolution 1920X1080FHD@60Hz
- + 10-point projection capacitive touchscreen
- + There are colored light bars all around
- + Single color, multi-color, and marquee can be set
- + COB light bar with soft and even lighting
- + Provides serial port for programming control
- + Customizable light bar modes based on application
- + Video interface: HDMI+VGA
- + Multiple assembly holes on the side and back
- + Support OS: Windows/Android/Linux
- + 2-year Warranty




Optional:

- No Touch
- AG Coating
- Video interface: Display Port
- All-in-one(Built in motherboard)



| TDS2739L Open-Frame Touchscreen Specifications(light bar) | |
|---|---|
| Model | 2739L |
| Color | Black/Silver |
| Diagonal | 27" |
| Active area | 597.6X336.15 (mm) |
| Dimensions | 644.2X388.4X 44.1(mm) |
| Resolution | 1920X1080FHD8@60Hz |
| Viewing Angle | Horizontal: 89°/89°,Vertical: 89° /89° |
| Number of Colors | 16.7M |
| Brightness | LCD Panel: 300nits,PCAP: 275nits |
| Contrast Ratio | 3000:1 |
| Touch Technology | PCAP (Projected Capacitive) - 10 Touch |
| Surface hardness | 7H(Mohs) |
| Light bar | Lighting mode: Standard:monochrome (Pink/Red/Yellow/Green/Orange /Ice Blue/ Blue/ White/) Optional:Multi-color(7 color rotation variations/Full color RGB rotation variation) |
| | Control mode : Standard:external control(Remote Control) Optional:Serial port control (Provides serial port communication protocol) |
| | Width:3mm Lighting angle: 180° Working voltage: 5V Waterproof level: IP20 |
| Speaker | 2*2W(Optional) |
| I/O Interface | 1*USB 2.0(for touch),1*HDMI,1*VGA,1*DC , 1*COM (Optional for light) |
| Input Voltage | AC:100-240 VAC, 50/60 Hz |
| Sealability | Touchscreen sealed to bezel |
| Mounting Options | Back VESA two groups of holes : 75mm&100mm Four sides has a set of fixing holes : 200mm |
| Drop Test | 450g steel ball falls from 1.2m without breaking |
| Weight (Unpackage) | 11KG |
| Shipping Dimensions | 720X 465X135(mm) |
| Temperature | Operating: 0 °C to 40°C; Storage : -20°C to 60°C |
| Humidity | Operating: 20% to 70% ; Storage: 10% to 80% |
| MTBF | 30,000 Hours |
| Power Supply | DC:12V5A |
| What' s in the Box | 1*USB cable,1*HDMI cable,1*DC cable,1*RJ45 OSD(Standard) L" (Side Mount) Brackets and w/Screws(Options) |
| Agency Approvals | FCC; CE; ROHS |

TDS2739L-PCAP



Dimensions are in millimeters

